

Printing date 22.10.2019

Version number 9

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CF 180
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SIKA AUTOMOTIVE FRANCE SAS

15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE

Tél.+33 (0)1 34 40 34 60

- · Further information obtainable from: DPT HSE +33 (0)1 34 40 34 60 safety@fr.sika.com
- · 1.4 Emergency telephone number:

ORFILA: +33 (0)1 45 42 59 59

+44 (0)1707 363899 (available during office hours).

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 G

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700) reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

*P264* Wash thoroughly after handling.*P273* Avoid release to the environment.

*P280* Wear protective gloves / eye protection / face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

*P391 Collect spillage.* 

(Contd. on page 2)



*Printing date* 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight $\leq$ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	25-50%
CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-25%
	Cycloaliphatic amine Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%

<sup>•</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

*In case of fire, the following can be released:* 

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

*Hydrogen chloride (HCl)* 

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

(Contd. on page 3)



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 2)

#### · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Inform personnel of risks associated with the product, the precautions to be taken and procedures to follow where an accident occurs.

- · Information about fire and explosion protection: Protect from heat.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection: Not necessary if room is well-ventilated.

(Contd. on page 4)



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 3)

#### · Protection of hands:



Protective gloves

#### · Material of gloves

Rubber gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty Colour: White

· Odour: Characteristic

· Change in condition

Melting point/freezing point:  $NA \circ C$ 

*Initial boiling point and boiling range:* >200 °C (DIN 53171)

*Flash point:* >110 °C (ISO 2719)

• Ignition temperature: >300 °C (DIN 51 794)

• Decomposition temperature: >200 °C (DIN 53171)

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

• Density at 25 °C: 0.80 g/cm³ (ISO 1675:1985)

· Solubility in / Miscibility with

water: Insoluble.

· organic solvents: Soluble in many organic solvents.

• 9.2 Other information No further relevant information available.

GB



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 4)

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Exothermic thermal decomposition.

Auto-catalytic thermal decomposition.

· 10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines.

Danger of polymerisation.

Exothermic polymerisation.

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Poisonous gases/vapours

At temperatures above 250°C, depolymerisation and the release of starting monomers can arise.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$ 700)

 Oral
 LD50
 11,400 mg/kg (rat)

 Dermal
 LD50
 >2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

CD



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 5)

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤700)

LC50 (96h) 1.3 mg/l (fish)

LC50 (48h) 2.1 mg/l (daphnia)

|LC50(72h)| > 11 mg/l (alga)

- · 12.2 Persistence and degradability No further relevant information available.
- · *Other information:* The product is not easily biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of the product by burning in a suitable incinerator or bury in an approved landfield following all applicable local and/or national regulations.

· European waste catalogue

20 01 27 paint, inks, adhesives and resins containing dangerous substances

- · Uncleaned packaging:
- · Recommendation:

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.

Disposal must be made according to official regulations.

#### SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN3077

· 14.2 UN proper shipping name

· ADR 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (epoxy resins)

· IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (epoxy resins), MARINE POLLUTANT

• IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (epoxy resins)

(Contd. on page 7)



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles.

· Label

· 14.4 Packing group

· ADR, IMDG, IATA Ш

· 14.5 Environmental hazards:

· Marine pollutant: Yes

*Symbol (fish and tree)* · Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): *Symbol* (fish and tree)

· 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles.

· Danger code (Kemler): · EMS Number: F-A.S-F

· Stowage Category Α

SW23 When transported in BK3 bulk container, see 7.6.2.12 · Stowage Code

and 7.7.3.9.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot ADR$ 

· Limited quantities (LQ) 5 kgCode: E1 · Excepted quantities (EQ)

> Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· Transport category 3

· Tunnel restriction code

· IMDG

5 kg · Limited quantities (LQ) · Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· UN "Model Regulation": UN 3077 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, SOLID, N.O.S. (EPOXY RESINS), 9, III

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category E2 Hazardous to the Aquatic Environment

• Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 8)



Printing date 22.10.2019

Version number 9

Trade name: CF 180

(Contd. of page 7)

- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

 ${\it Skin Sens.} \ 1: {\it Skin sensitisation-Category} \ 1$ 

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.

GB